

● Specifications

Display contents :

16 Characters × 2 Lines

Character format : 5 × 8 dots

Driving duty : 1/16D


Provided version :

TN, STN Reflective

With EL or LED

EL/100VAC, 400Hz; LED/4.2VDC

● Block Diagram



● Absolute Maximum Ratings

Item	Symbol	Min.	Typ.	Max.	Unit
Power Supply Voltage	V _{DD} -V _{SS}	-0.3	-	7.0	V
LCD Driving Voltage	V _{DD} -V _{EE}	V _{DD} -15.0	-	V _{DD} +0.3	
Input Voltage	V _{IN}	-0.3	-	V _{DD} +0.3	
Operating Temp.	T _{OP}	0	-	50	
Storage Temp.	T _{ST}	-20	-	70	

● Electrical Characteristics

Item	Symbol	Test Condition	Min	Typ.	Max.	Unit
Input High Voltage	V _{IH}	-	2.2	-	V _{DD}	V
Input Low Voltage	V _{IL}	-	-0.3	-	0.6	V
Output High Voltage	V _{OH}	I _{OH} = 0.205mA	2.4	-	-	V
Output Low Voltage	V _{OL}	I _{OH} = 1.2mA	-	-	0.4	V
Supply Current	I _{DD}	V _{CC} = 5.0V	-	1.3	3.0	mA

● Mechanical Specifications

